RESEARCH ARTICLE | AUGUST 17 2023

Synthesis and experimental investigation of Magnetorheological (MR) fluid for damper **FREE**

Prashant Narwade 🖙; Ravindra Deshmukh; Manoj Wagh; Vijay Kumar Sukhwani

Check for updates

AIP Conference Proceedings 2890, 020007 (2023) https://doi.org/10.1063/5.0157075



CrossMark rt

Articles You May Be Interested In

Design and modelling of radial flux MR damper with radial basis function based neural network *AIP Conference Proceedings* (June 2023)

Comparison of axial and radial flux piston designs for vehicular applications with MR damper

AIP Conference Proceedings (June 2023)

Modeling of MR Fluids and Devices

AIP Conference Proceedings (July 2008)



500 kHz or 8.5 GHz? And all the ranges in between.







Synthesis and Experimental Investigation of Magnetorheological (MR) Fluid for Damper

Prashant Narwade^{1,a}, Ravindra Deshmukh^{2, b}, Manoj Wagh^{3,c} and Vijay Kumar Sukhwani^{4,d}

¹D.V.V.P College of Engineering, Ahmednagar, India ²Jawaharlal Nehru College of Engineering, Aurangabad, India ³D.V.V.P College of Engineering, Ahmednagar, India ⁴Government College of Engineering, Ujjain, M.P., India

- a) Corresponding author: narwadeprashant@gmail.comb) prithardeshmukh@rediffmail.com
 - c) profmpwagh@gmail.com
 - d) wienie ameil and
 - d) v1sukhwani@gmail.com

Abstract. Magneto-rheological (MR) fluids have been an attractive field of study since the invention of the smart fluid. This paper presents the characterization and development of MR fluid prepared by immersing ferromagnetic elements in carrier oil. Micron-sized atomized iron and carbonyl iron surfaces are coated with guar and xanthan gum to counter issues with sedimentation, cluster formation, and cake formation of the MR fluid (MRF). A variety of MR fluid mixtures are organized by means of amalgamation of base fluids (Paraffin oil and silicone oil), ferromagnetic particles, and additives. The morphology of carbonyl iron has a flake-like structure and atomized iron dust forms a smooth granular configuration. MR fluid comprising Xanthan gum coated iron particles demonstrated enhancement in sedimentation. Additionally, by providing power, the magnetism of the magnetic piston is investigated, and discovered that magnetic flux density rises with the applied current in Ampere. The sedimentation results demonstrate that MR Fluid-4 and MR Fluid-3 enhanced the sedimentation rate substantially more than the others. Paraffin oil-based MR (MR Fluid-4) presented better viscosity than any other fluids. The fluid's high viscosity property contributes to increasing the resisting force of the MR damper system. Lastly, the performance of the MR damper is investigated by applying currents of 1A and 1.5A at various excitation velocities. MR damper enhances dampening force by 15% and decreases overall vibration acceleration by 30% when operating at 1.5A current.

Keywords-Damper, Magneto-rheological (MR) fluid, Shear stress, Sedimentation, Synthesis.

INTRODUCTION

An intelligent fluid known as a magneto-rheological (MR) fluid instantly modifies its rheological characteristics when subjected to an external magnetic field. This reversible, regulated transition occurs rapidly with minimal energy input. Ferromagnetic particles smaller than a micron are dispersed at random in the carrier oil. [1,2].

Ferromagnetic particles, carrier fluids, additives are the three basic components of MR solution. Carbonyl iron concentrate with a high magnetic permeability and saturation magnetization are frequently utilized for mixing in oil. As the base (carrier) fluid, low viscosity lubricants like mineral, silicone, and synthetic oils are used. Surfactants are frequently used as additives to reduce the aggregation of ferromagnetic ingredients or to slow down the rate at

10th National Conference on Recent Developments in Mechanical Engineering AIP Conf. Proc. 2890, 020007-1–020007-11; https://doi.org/10.1063/5.0157075 Published by AIP Publishing. 978-0-7354-4608-3/\$30.00

020007-1

which they settle [3]. Due to the particle's high density and tendency to settle or silt, the use of additives is an important consideration that, if ignored, could cause the device to become unusable. When a magnetic field is provided, the particles line together in a pattern to form chain links, and the MR fluid acts like a viscoelastic solid.. Lacking magnetism, the fluid functions exactly like regular hydraulic fluid. This aligned chain-like structure offers great resistance to the oil layer thus increasing the viscosity within a short time. Such fluids have received increasing interest recently for applications like suspension systems, brakes, and clutches [3].

The MR damper has a significant amount of potential for semi-actively controlled variable damping with little power. Figure 1(a) shows the magnetic piston developed for the MR damper (Magneto-rheological damper) and Figure 1(b) shows the assembly of the retrofit MR damper. Only the damper part is replaced in a conventional shock absorber.



(a) (b) FIGURE 1. (a) Magnetic Piston (b) Assembled MR Damper

In this article, four different MR fluids are developed by using different material combinations. With the help of a literature review, magnetic particles, coating gums, and carrier fluids are identified. The presented MR fluids are visually investigated for sedimentation analysis in the sedimentation analysis section. Composition of MR fluid is discussed in a methodology section. In the results and discussions, the change in viscosity of all fluids and its impact on damping force is evaluated. Finally concluding comments are drawn in the final section

LITERATURE REVIEW

The authors are motivated to employ their knowledge of magneto-rheological fluids, which Rabinow discovered in 1948, in a variety of applications [1]. A MR fluid with variable viscosity as a function of current can effectively replace a conventional viscosity-based hydraulic system. It responds quickly, consumes minimal electrical power, and offers controlled mechanical power output. [2]. Micro sized iron particles that aren't properly dissolved in the base fluid cause sedimentation problems and it is very important for the synthesis of MR fluid [3]. The particle structure in the presence of magnetic field provides shear stress to the MRF. When particle sizes increase, MRF shear stress rises. However, due to a problem with sedimentation, the use of larger sized particles is restricted. [4]. Natural gum is utilized as a surface coating to prevent the MR fluid from adhering, corroding, and sedimenting. Carrier fluids are blended with grease and other thixotropic additives. Iron particles settle down at the bottom when MR fluid is not in use for several days and additives will help in solving this [5]. A MR damper is a simple, semi-active device containing MR fluid and having the capacity to change damping force within milliseconds. It provides better ride comfort than conventional suspension systems [6]. Applications for MR dampers can be found in a variety of civil constructions, including buildings and bridges, as well as in vehicles and railway systems. According to displacement and frequency of vibrations, damping force can be generated by supplying required voltage [7]. The MR damper system is operated for all types of input excitations by controlling the current supplied to MR damper RD-8040-1 and can be used to design a seat suspension for fatigue-free rides [8]. To develop an organic oil blend, silicone oil is blended with environmentally safe natural organic oils like sunflower and cottonseed. Considering viscosity, the cottonseed oil blend-based MR fluid outperforms the sunflower-based fluid [9].

21 August 2023 14:58:02

A unique electronically controlled power steering system that makes use of MR fluid was proposed by Park and Jung. They conducted trial investigation to prove the feasibility of the proposed system [10]. Umit Dogruer investigated an off-highway, high mobility vehicle's semi-active MR fluid damper. He built a quarter-car model with two degrees of freedom and employed variety of control algorithms to manage the MR fluid damper. The Bingham Plastic model is used to mimic the behaviour of the MR fluid, and a magnetic finite element analysis is used to determine the magnetic field circulation [11]. Lin et al. assessed the effectiveness of a retrofitted MR damper under dynamic loading conditions. Modified Bouc-model is developed to check functionality of the MR model. Moreover, they used an experimental structure with MR damper [12].

On a Stryker vehicle, authors tested the MR semi-active suspension system. An algorithm was used to test the full model, which included eight dampers and controls [13]. Nabaglo conducted both experimental and numerical research on MR damper control system with low energy requirements. The goal was to significantly lessen vertical acceleration in the presence of moments and forces operating on the vehicle under various riding circumstances [14]. The theoretical characterization of a lightweight MR damper is explored by Avdar et al. They discovered that the MR damper's controllability enables them to alter the damping necessary for various frequencies and lowers noise at resonance [15]. PID control algorithms are used to study the impact of road disruptions. Inputs from step and impulse road disturbances perform very well with PID controllers. It cannot, however, adapt as the circumstance does. A fuzzybased PID controller produced better outcomes [16]. Skyhook, fuzzy logic, LQG, and sliding mode controllers are some of the controllers that can be implemented with MR dampers. Dong et al. claimed that the best suspension performance is provided by sliding mode-controlled MR dampers [17]. For variable displacement engines, an engine mount utilizing an MR damper is developed and offered the best control over vibration minimization [18]. By modulating the magnetic field, author demonstrated that MR dampers have good damping characteristics [19]. Artificial neural network MR damper models were investigated by the authors. They came to the conclusion that the proposed ANN could model MR dampers more effectively than existing parametric models. [20]. Fuzzy logic controller was tested in a car suspension system and proved that fuzzy logic controller offers appreciably superior ride comfort [21].

Avinash et al. compare the damper's performance by varying the fluid environment, namely, MR fluid damping, viscous damping, and air damping and reported that MR fluid dampers provide better-damping presentation [22]. When properly adjusted, the Skyhook algorithm outperforms the passive suspension in terms of ride comfort and vehicle handling by managing the MR damper with a range of current values [23]. Authors proved that the developed hybrid MR damper could absorb shocks in severe road conditions also [24–25]. An electromagnetic field study of the constructed damper was performed using the ANSYS programme, and it was found that a damping force of 6517 N was achieved at 1.5 A. It was validated experimentally and found that the maximum damping force reaches 6838N at a damping coefficient of 300 kN-s/m [26]. In the quarter car concept, the active seat suspension is modeled with the equivalent damping model and the Bingham model. Initially a bump input with varying degrees of road roughness is applied. The Equivalent Damping Model is found to perform better than the damper behaviour of the Bingham model in both circumstances, i.e., bump input and random road input [27]. Neural network based model method has an improved capacity to forecast the damper force for a more complex excitation [28]. H. Zambare et al. compared the analytical design of the passive suspension and semi-active suspension using the Bouc-Wen, Dahl, and Bingham hysteresis models. The observations show that the Bouc-Wen model is the most practical and suitable model for developing a semi-active suspension system. [29].

Authors have illustrated MR fluid properties or studied MR damper responses to excitation using software models. MR fluid developed by authors is not experimentally examined for developed MR damper. The selection criteria for the MR fluid in the MR damper of the suspension system are the subject of an experimental investigation in the current paper.

METHODOLOGY

Composition of MR Fluid

This chapter focuses on the process of developing trustworthy MR Fluid capable of working with MR damper. Magnetic material with high purity such as carbonyl iron powder and iron dust appears to be the main magnetic practical composition. Material composition and steps required for MR fluid preparation are shown in Figure

2. The enduring component of MR fluid is made up of the base (carrier) liquid, which could consist of silicone oils, mineral oils, or paraffin oils.



FIGURE 2. Structural outline for preparation of MR Fluid

For the fluid combinations stated in Table 1, carbonyl and atomized iron powder typically in the range of 0.1 to 10μ m have been employed in the current study. Guar gum and xanthan gum powder are employed to coat the iron particle surfaces, enhancing the fluid's performance. The carbonyl iron is donated by Industrial Metal Powders India Pvt. Ltd. in India, and the atomized iron dust is donated by Höganäs AB in Sweden. According to Table 1, the density of atomized iron dust coated with guar gum is larger than that of samples 1 and 2. Sedimentation of fluid increases with an increase in density. Hence only carbonyl iron samples are used further for fluid combinations.

TABLE 1.	Surface	coating	of	ferromagnetic	material
----------	---------	---------	----	---------------	----------

Sample No.	Magnetic particles with coating	Density (gm/cm ³)
Sample 1	Xanthan Gum coated Carbonyl Iron	1.48
Sample 2	Guar Gum coated Carbonyl Iron	1.40
Sample 3	Guar Gum coated Atomized Iron	2.82

Field Emission Scanning Electron Microscopy (FESEM), which is available at Savitribai Phule Pune University, is employed to observe the particle outlines and dimensions. Size and shape of all ferromagnetic constituents is observed at magnification of 5000x as shown in Figure 3. Particle dimensions of guar gum and xanthan coated carbonyl iron powder vary from 1 to 10 microns, whereas those of guar-coated atomized iron dust vary from 5 to 20 microns. Larger iron particles have stronger magnetic fields than smaller iron particles, but they have tendency to go down at the bottom of fluid resulting in sedimentation.



(a) (b) (c) FIGURE 3. Microscopic images at 5000x of ferromagnetic particles (a) Sample 1, (b) Sample 2, (c) Sample 3

The spherical, guar gum coated atomized iron dust (Sample 3) have a smooth surface and a big size of 20 microns. With guar gum and xanthan coated carbonyl iron powder (Sample 1 and 2), a flakes-like structure can be seen and a particle size of fewer than 10 microns is obtained. Flake structure helps to increase the strength of the bond under a magnetic field which further leads to increased fluid viscosity. It is observed from the experiments that, Xanthan gum coating is more effective than guar gum coating in minimizing the sedimentation of MR fluid. Furthermore, three potential non-magnetic oils are specified, as listed in Table 2, including silicone oil, synthetic oil, and paraffin oil. The density of paraffin oil is more than the density of silicone and synthetic oil.

Base fluid	Kinematic Viscosity (centistokes)	Density (gm/cm ³)
Silicone oil	11.2	0.771
Synthetic oil	36.2	0.794
Paraffin oil	171	0.823

ΓAI	BLE	2.	Base	fluid	charact	eristics

Blended Base Fluid	Additives	Base fluid	Density (gm/cm ³)
Fluid A	Oleic acid+ Grease	Synthetic oil	0.822
Fluid B	Stearic acid+ Grease	Paraffin oil	0.871
Fluid C	Ethanol + Glycerine	Silicone oil	0.916

According to Figure 4 (a), base fluid and additives are properly combined using a mechanical stirrer. Figure 4 (b) illustrates how the Brookfield DV-E viscometer is used to determine the kinematic viscosity of these stirred fluids. All the ingredients are stirred for 12 hours to prepare the fluid, as shown in the flow structural diagram.



(a)



FIGURE 4. (a) Mechanical Stirrer (b) DV-E Viscometer

To synthesize the MR fluid, quantities of paraffin, silicone, and synthetic oil are used as the base fluid. The kinematic viscosity of paraffin oil is the highest, measuring 171 cSt. These primary fluids are combined with additive mixtures, as shown in Table 3, to improve the rheological and sedimentation characteristics of MR fluid. Developed fluid mixtures are evaluated on a viscometer to see how shear stress increases as the shear rate changes. Figure 5 demonstrates that Fluid B has a higher shear stress level. It is observed that base fluid paraffin oil and synthetic oil perform better than the silicone oil mixed with glycerine and ethanol. Density of Fluid C is more but the required

21 August 2023 14:58:02

shear stress is less than the other two. Shear stress rises with fluid viscosity, which enhances the dampening properties of the damper, consequently Fluid A and Fluid B are chosen for MR Fluid experiments.



FIGURE 5.Shear stress Versus shear rate of blended base fluids

Synthesis and development of MR fluid

The essential components of fluid blended with additives are paraffin oil and synthetic oil. To develop MR fluid, guar and xanthan gum coated carbonyl iron are added to carrier fluid. Table 4 provides an overview of the four prepared MR fluid types. Since larger particles will ultimately settle down, the size of guar gum surface coated atomized iron dust, which ranges from 5 microns to 20 microns, is not taken into consideration. Fluids are uniformly prepared by stirring various MR fluid combinations at 900 rpm continuously for 12 hours.

TABLE	4.	MR	fluid	types
	•••		11010	c peo

MR Fluid	Blended Base Fluid	Magnetic particles
	with Additives	
MR Fluid-1	Fluid A	Carbonyl Iron with
		Guar Gum coating
MR Fluid-2	Fluid A	Carbonyl Iron with
		Xanthan Gum coating
MR Fluid-3	Fluid B	Carbonyl Iron with
		Guar Gum coating
MR Fluid-4	Fluid B	Carbonyl Iron with
		Xanthan Gum coating

SEDIMENTATION ANALYSIS

Due to the difference in densities, the particles settle and leave relatively clear volume of carrier fluid behind. To measure the settling rate of iron particles, visual inspection is carried out to compare the heights of the dispersed phase (a) and the height of the settled phase (b) across different time frames. A illustrative experiment conducted for the sedimentation investigation is shown in Figure 6. Sedimentation ratio (SR) of settled particles is calculated with the help of Equation 1. Where value 'a' is dissolved phase and (a + b) represents total height of the MR fluid. % $SR = \frac{a}{a+b} x \ 100$ (1) As shown in figure 6, a 50 ml cylinder had been filled with all the developed MR Fluids, and the mixture was let to stand for 120 hours. The volume of magnetic particles deposited at the bottom is depicted in Figure 6a.



FIGURE 6. (a) Sediment iron particles(b) Illustrative image of sedimentation

Figure 7 demonstrates how MRFluid-1 has a higher sedimentation ratio than other fluids. In MR Fluid-1, a synthetic oil-based fluid, iron particles settled quickly and reached 64%. In contrast to the other four fluids, the sedimentation ratio of carbonyl iron coated with xanthan gum powder in MR Fluid-4 slowed significantly. The elevated shear stress change caused by paraffin oil and grease (MR Fluid-4) and high density of Paraffin oil than Synthetic oil combination, particle settling speed of MR Fluid-4 is slower than Synthetic oil combination.



FIGURE 7. Sedimentation ratios of coated iron particles versus Time

MAGNETIC FLUX DENSITY OF ELECTROMAGNETIC PISTON

The magnetic field's flow is essential for an MR damper to perform well. The desired damping force of the MR damper is thus determined by the electromagnetic flux density of the magnetic piston. To improve the magnetic flux density and magnetic force of the MR damper, magnetic permeability is a crucial component. Equation 2 is used to compute the magnetic flux density. In the equation H is magnetic field intensity, "I" is current in Ampere, "*l*" *is* the length of the magnetic circuit on the piston, and "N" represents the number of turns. The length of copper wire winding on the magnetic piston is 26 mm and 320 numbers of turns are wound on the piston. The relative permeability of material is symbolized by " μ_r " which is 100 and permeability of free space is represented by " μ_0 " which is $4\pi \times 10^{-7}$ (Henries per meter).

Magnetic flux density $B = \mu_r x \mu_o x H$ (Tesla) (2)

Where,

 $\mu = \mu_r \times \mu_0$

 $H = \frac{NI}{l}$

It is viewed from the Fig.8 that the magnetic flux density increases with increase in current of magnetic coil. Magnetic flux density increases linearly up to 1.2 A current and saturation point occurs at 1.8 A. Hence MR fluid is activated from current 0.1 A to 2 A.



FIGURE 8. Magnetic flux density versus current

RESULTS AND DISCUSSION

Measurements of the rheological features of generated MR fluids are carried out by employing magnetism with the aid of current in the ampere. The rheology of MR fluids instantly changes from a free flowing low viscosity to high viscous liquid with controllable viscosity in centipoises when they are in close proximity to a magnetic field. Figure 9 demonstrates how fluids have high viscosity when a magnetic field is a present and low viscosity when one is not. The MR Fluid-4 with paraffin oil as the base oil and grease, stearic acid as additives mixed with xanthan gum coated carbonyl iron can create viscosity around 1800 centipoise, while viscosity of MR fluid-1 and MR fluid-2 with synthetic oil as base oil, mixed with additives grease, Oleic acid was limited to 1600 centipoise. After a value of 1.08 T magnetic flux density, MR Fluid-3 viscosity is lower than MR Fluid-4 but exhibits similar rheological characteristics. For MR damper testing, MR Fluid-4, which becomes highly viscous under magnetic fields, is added to the MR damper cylinder.



FIGURE 9. Viscosity versus Magnetic flux density for all four fluids

Magneto-rheological damper (MR damper) having an electromagnetic piston fitted in a cylinder filled with magneto-rheological (MR) fluid is used for testing the selected MR Fluid-4.MR damper is operated at current of 1.0A and 1.5A and compared with passive damper.



FIGURE 10. Damping force of Passive damper and MR damper versus Velocity

The damping performance of the MR damper is observed on the test rig under different excitation velocities, by supplying a current of 1A and 1.5A. Dampers reduce vibrations by dissipating the energy of vibrations. When a vehicle hit a bump on the road, the damper's piston advances to absorb the vibration and gets compressed. This compressed force experienced by the damper is compression force and the force that a shock absorber experiences as it decompresses and then expands back to its original state is known as rebound damping. Damping force as shown in Figure 10 is compression force required to reduce the vibration excitation. Rebound damping is not considered in the paper. It is observed that the MR damper outperforms the passive damper at all velocities of vibration. The damping force obtained at 1.5 A current is 15% more and at 1.0A is 11% more than the damping force obtained with a passive damper. Moreover, as demonstrated in Figure 11, the FFT Analyzer (Fast Fourier Transform spectrum analyzer) is employed to acquire the vibration acceleration. Initially, when the vehicle hit a bump, all dampers show an acceleration of about 1.4 m/s2, but after 10 Hz frequency amplitude of the MR damper at 1.5A current is much lower than the passive damper. The acceleration of the MR damper obtained at 1.0A current is slightly higher than that of 1.5 A.



FIGURE 11. Acceleration of Passive damper and MR damper at different frequencies

CONCLUSION

In order to conduct an experimental examination on sedimentation, shear stress, viscosity, damping force, and vibration acceleration, this study includes four MR fluid samples. Samples are grouped using a combination of surface coated magnetic particles, carrier fluids, and additives. The statement is that the lowest sedimentation ratio is noticed in MR Fluids 4 and 3, that are using paraffin as the carrier fluid. When the current continuously increases, the magnetic flux density rises resulting increase in viscosity. It has been observed that all developed MR fluids became more viscous as magnetic flux density increased. Higher shear stress level above 250 Pa is observed in Paraffin based oil mixed with grease and stearic acid. Shear stress of less than 90 Pa is observed in Silicone based oil is not considered further for the fluid combination. Hence paraffin based MR Fuid-4 mixed with additives grease, stearic acid, and xanthan gum coated carbonyl iron illustrated a viscosity of more than 1800 centipoise. The fluid's high viscosity feature aids in boosting the MR damper's damping force. A damping force of about 400N is observed at 3.5 m/s velocity with the help of an MR damper. The damping force of the MR damper supplied with 1.5A current is 15% more than the damping force obtained by the passive damper. The acceleration amplitude of the MR damper with 1.5A current outperforms the passive damper by reducing acceleration by 30%.

REFERENCES

- [1] J. Rabinow, "The Magnetic Fluid Clutch", Transactions of the American Institute of Electrical Engineers, **67(2)**, pp.1308-1315 (1948).
- [2] A. Spaggiari, "Properties and applications of Magnetorheological fluids", Frattura ed Integrità Strutturale, 7(23), pp. 57–61.
 doi: 10.3221/IGF-ESIS.23.06 (2013).
- [3] V.K. Sukhwani and H. Hirani, "Synthesis and characterization of low cost MR fluids", Proc. SPIE 6526, Behavior and Mechanics of Multifunctional and Composite Materials65262R (2007).
- [4] C. Sarkar and H. Hirani, "Particle Dynamics of Polydisperse Magnetorheological Fluids", Smart Science Vol. 3, No. 4, pp. 176-187(2015).
- [5] W. Wu, B. Zhao, Q. Wu, L. Chen, and K. Hu, "The strengthening effect of guar gum on the yield stress of magnetorheological fluid", Smart Materials and Structures, 15(4), pp.N94-N98 (2006).
- [6] H. Metered, P.Bonello, and S.O.Oyadiji, "The experimental identification of magnetorheological dampers and evaluation of their controllers", Mechanical Systems and Signal Processing, 24(4), pp.976–994 (2010).
- [7] D. Wang, and W. Liao, "Magnetorheological fluid dampers: a review of parametric modeling", Smart Materials and Structures, **20**(2), pp.023001 (2011).
- [8] R.M. Desai, M.E.H. Jamadar, H. Kumar, S. Joladarashi, S.C. Rajasekaran and G.Amarnath, "Evaluation of a commercial MR damper for application in semi-active suspension", SN Applied Sciences volume 1, Article number: 993 (2019), doi:10.1007/s42452-019-1026-y.
- [9] R. Jinaga, T. Jagadeesha, S. Kolekar, and S. Choi, "The Synthesis of Organic Oils Blended Magnetorheological Fluids with the Field-Dependent Material Characterization", International Journal of Molecular Sciences, **20**(**22**),p.5766 (2019)
- [10] Y. Park, and B. Jung, "Development of damper for new electronically controlled power steering system by magnetorheological fluid", MRSTEER, International Journal of Vehicle Design, 33(1/2/3),pp.103-109 (2003).
- [11] UmitDogruer, F.Gordaninejad, and C. Evrensel, "A New Magneto-rheological Fluid Damper for High-mobility Multipurpose Wheeled Vehicle (HMMWV)", Journal of Intelligent Material Systems and Structures, **19(6)**, pp.641-650 (2007).
- [12] Pei-YangLin, P.N. Roschke and Chin-Hsiung, "System Identification and Real Application of the Smart Magneto-Rheological Damper.In: Intelligent Control", IEEE International Symposium on, Mediterrean Conference on Control and Automation, (2005).
- [13] Andrea C. Wray, Alexander R. Jimenez, Eric Anderfaas, Brian Hopkins and Peter LeNoach, "Magneto-rheological fluid

- [14] NabagloTomasz, "Controller of magneto-rheological semi-active car suspension", SAE 2006 Automotive Dynamics, Stability and Controls Conference and Exhibition, SAE Technical Paper, 01-1969 (2006).
- [15] G. Aydar, C. Evrensel, F. Gordaninejad, and A. Fuchs, "A Low Force Magneto-rheological (MR) Fluid Damper: Design, Fabrication and Characterization", Journal of Intelligent Material Systems and Structures, 18(12), pp.1155-1160 (2007).
- [16] B. Kasemi, M. Mahbubur Rashid, and S. Fathima "Fuzzy-PID Controller for Semi-Active Vibration Control Using Magnetorheological Fluid Damper", Proceedia Engineering, 41, pp.1221-1227 (2012).
- [17] X. Dong, M. Yu, C. Liao, and W. Chen, "Comparative research on semi-active control strategies for magneto-rheological suspension", Nonlinear Dynamics, 59(3), pp.433-453 (2009).
- [18] H. Mansour, S Arzanpour, M.F. Golnaraghi, and A.M. Parameswaran, "Semi-active engine mount design using auxiliary magneto-rheological fluid compliance chamber", Vehicle System Dynamics .49(3), (2011).
- [19] Jorge de-J Lozoya-Santos, Ruben Morales-Menendez, Ricardo Ramirez-Mendoza, Juan C Tudón-Martinez, OlivierSename, and Luc Dugard, "Magneto-rheological damper-An experimental study", Journal of Intelligent Material Systems and Structures,23 (11),pp.1213-1232 (2012).
- [20] Tudón-Martínez, JC, J de J Lozoya-Santos, R Morales-Menendez, and RA Ramirez-Mendoza, "An experimental artificialneural-network-based modeling of magneto-rheological fluid dampers", Smart Materials and Structures, 21(8),085007,(2012).
- [21] Shojaei, Alisina, H Metered, SiamakShojaei, and S OlutundeOyadiji, "Theoretical and Experimental Investigation of Magneto-Rheological Damper based Semi-Active Suspension Systems", International Journal of Vehicle Structures & Systems (IJVSS), 5(3-4), pp.109-120 (2013).
- [22] B. Avinash, S. Shyam Sundar, and K.V.Gangadharan, "Experimental study of damping characteristics of air, silicon oil, magneto rheological fluid on twin tube damper", Procedia Materials Science, 5, pp.2258-2262 (2014).
- [23] P. Krauze, J. Kasprzyk, J. Rzepecki, "Experimental attenuation and evaluation of whole body vibration for an off-road vehicle with magnetorheological dampers", Low Frequency Noise & Vibrations, 38(2), pp.852-870, (2019).
- [24] AMA Soliman and MMS Kaldas, "Semi-active suspension systems from research to mass-market- A review", Journal of Low Frequency Noise, Vibration and Active Control, 40(2), pp. 1-19, (2021).
- [25] Pinjala Devikiran, N.P. Puneet, AbhinandanHegale and Hemantha Kumar, "Design and development of MR damper for two wheeler application and Kwok model parameters tuning for designed damper", Proceedings of the Institute of Mechanical Engineers, Part D: Journal of Automobile Engineering, 236(7), pp. 1-12 (2022).
- [26] Guoliang Hu, Hao Liu H, Jinfu Duan, Lifon Yu, "Damping performance analysis of magnetorheological damper with serialtype flow channels", Advances in Mechanical Engineering, 11(1), doi:10.1177/1687814018816842 (2019).
- [27] M.E.H. Jamadar, R.M. Desai, R.S.T. Saini, H. Kumar, S. Joladarashi, "Dynamic analysis of a quarter car model with semiactive seat suspension using a novel model for magneto-rheological (MR) damper", Journal of Vibration Engineering and Technology, 9(1), pp.161-176. doi:10.1007/s42417-020-00218-1(2021).
- [28] S. Wei, J. Wang, and J. Ou, "Method for improving the neural network model of the magnetorheological damper", Smart Mechanical Systems and Siganl Processing, 149, https://doi.org/10.1016/j.ymssp.2020.107316 (2021).
- [29] H. Zambare, A. Khoje, S. Patil, A. Razban, "MR damper modeling performance comparison including hysteresis and damper optimization", IEEE Access, 9:24560-24569, doi:10.1109/access.2021.3057174 (2021).

Application of Artificial Intelligence and IoT to Membrane Bioreactor (MBR) and Sewage Treatment Plant



Manoj Wagh, Dnyaneshwar Vasant Wadkar, and Prakash Nangare

Abstract A membrane bioreactor (MBR) is a capable treatment technology that consists of an activated sludge process (ASP) emerging with membrane filtration which retains the reduced biomass. MBR is an emerging treatment technology to treat sewage wastewater and reuse the water for various purposes like gardening, toilet flushing, farming, etc. In this paper, a design of the sewage treatment plant is proposed by using MBR technology. To achieve promising and effective results, the traditional design method has been replaced by modern techniques such as wireless sensor networks and the Internet of Things (IoT) software platform to carry out the analysis of sullage wastewater. It concludes that the traditional design system is influenced by the integration of IoT. Further, this paper gives insight into the application of Artificial intelligence (AI) for curtailing the complications in sewage treatment.

Keywords Artificial intelligence · Internet of Things · Membrane bioreactors · Sewage treatment plant · Wireless sensor networks · Wastewater

1 Introduction

Sewage is the wastewater generated by the community of human beings. Around 70% of freshwater consumption is converted into wastewater. Wastewater is contaminated by domestic, industrial, and commercial use that changes its parameters continuously such as COD, BOD, pH, hardness, TSS, etc. Water scarcity is a big challenge to fulfill the per capita demand of the city. Hence, there is an urgent need to treat wastewater and utilize it effectively so that the water demand can be fulfilled. It is observed

D. V. Wadkar · P. Nangare

M. Wagh (🖂)

Department of Civil Engineering, Dr. Vithalrao Vikhe Patil College of Engineering, Ahmednagar, Maharashtra, India

e-mail: profmpwagh@gmail.com

Department of Civil Engineering, AISSM'S College of Engineering, Savitribai Phule Pune University, Pune, Maharashtra, India

[©] The Author(s), under exclusive license to Springer Nature Switzerland AG 2024 P. M. Pawar et al. (eds.), *Techno-societal 2022*, https://doi.org/10.1007/978-3-031-34644-6_3

that 99% of water is characterized by the rate of flow of its biological, chemical, and physical factors (BOD, COD, pH, hardness, conductivity, turbidity, acidity, DO, TDS, TSS). The sewage wastewater systems can meet the demand for freshwater in smart cities by treating and managing wastewater with the help of Artificial intelligence (AI) and Internet of Things (IoT) sensors. AI and IoT have several influential and hands-on tools to overcome various complex problems related to wastewater treatment [1]. Nowadays, several researchers have implemented AI and IoT technologies because of convenient operation, high speed, high accuracy, and no issues related to the physical problem [2]. AI implemented for seed, crop, leaf, stem, fruit infection [3]. AI is also applicable for the financial sector to predict financial capital [4]. AI can resolve various practical issues related to various engineering disciplines such as civil engineering, environmental engineering, etc. To improve the quality of wastewater and drinking water AI was implemented [5]. The ground water contamination is detected using AI [6]. AI plays an important role to enhance the quality of water by assessing river water, wastewater recycling and water resource engineering [7]. Further, AI is used to find out the characteristics of saline water and to treat the saline water [6, 7]. To detect the machine fault, AI technology is convenient [8]. AI has application in an integrated vehicle health management (IVHM) for aerospace to identify the primary challenges related to paradigm [9]. The process of removing a contaminant from wastewater and household sewage both runoff and domestics are called Sewage treatment [8, 9]. The sewage wastewater treatment is the significant steps to reduce the pollution and promote the water quality [10]. Sewage is the complex waste affected by microbiological, physical and chemical factors variability which requires appropriate treatment technology to operate the sewage treatment plant [10, 11]. Membrane bioreactor (MBR) has made great attention owning to its very high efficacy and is a capable treatment technology which consists of activated sludge process (ASP) emerging with membrane filtration which retain the reduced biomass [11]. MBRs technology is observed as significant fundamentals of advanced effluent repossession and recycle technology and are comprised in a numeral of prominent schemes worldwide [12]. MBR having energy saving efficiency and footprint over conventional processes such as activated sludge process (ASP) oxidation pond, etc. MBR consists of ASP and a membrane detached method [13]. MBR functioning analogous to traditional ASP, and there is no requirement of sedimentation and filtration identical to slow sand filtration (SSF) [14]. Small pressure membrane purification whichever micro-filtration (MF) or ultra-filtration (UF) were implemented to distinct wastewater from ASP [15]. MBR configuration consists of submerged membrane or external circulation (side stream configuration) [16]. Submerged membrane often applied in municipal wastewater treatment [17]. Submerged membrane bioreactor consists of plate membrane module or hollow fibre [18]. Sufficient preliminary treatment was essential to avoid the clogging (Membrane fouling) [19]. 12–15 g/s is recommended for more concentration otherwise it will lead to the functioning problem and decreased oxygen transfer efficiency [20]. Hydrodynamic condition, type of membrane salient feature of module is highly responsible for the clogging of MBR. Due to the bacteriological digestion molecular weight of present substance may increase [21]. The emerging technology

Application of Artificial Intelligence and IoT to Membrane Bioreactor ...

interacts with active sludge and detached sludge and liquid wastewater [22]. ASP consist of screening aeration, clariflocculator and rapid sand filter but still sludge is generated on a large scale this problem can be solved easily using cutting-edge technology such as membrane bio technology which enhance organic treatment. This technology having scope to degrade the parameters of highly contaminated wastewater, dairy industry, sugar industries food processing industries etc. The technology becoming popular day-by-day due to less space is required for installation, instant operation, very less sludge generation and quality of treated parameters as per the central pollution control board norms.

This process involves physical, chemical, and biological methods that remove respective contaminants also produce clean and safe water. In this paper, IoT and Artificial Intelligence (AI) based prediction models were implemented to monitor the sewage treatment plant.

2 Preparation of Your Paper

Figure 1 shows the location of Imagica STP plant Khopoli-Pali Road, SH 92, Sangdewadi, Maharashtra, India. The layout of the Imagica STP plant has been mentioned in Fig. 2. A row sample of sewage was collected in a container and kept in the refrigerator (Fig. 3). Analysis of sewage wastewater was carried out to find out the characteristics of sewage wastewater (Table 1).

Surrounding is extremely contaminated if industrial waste is discharged without treatment. Portable water is the basic need of human beings. The Maharashtra government treat 22% sewage collected. The remaining 78% row sewage predisposed into



Fig. 1 Site location of STP plant



Fig. 2 Flow diagram of STP Imagica Water Park



Fig. 3 Row sewage collection

Application of Artificial Intelligence and IoT to Membrane Bioreactor ...

Tuble I Chemiea	able 1 Chemical characteristics of sewage wasewater					
S. No	Test parameters of untreated sample	Laboratory result				
1	pH value	7.12				
2	Electrical conductivity, ds/m	0.631				
3	Turbidity, NTU	9.0				
4	TDS, ppm	321.4				
5	COD, mg/lit	723				
6	BOD (at 3 day), mg/lit	192				
7	DO, mg/lit	1.42				
8	Total hardness as CaCO ₃ , mg/lit	294				
9	Total alkalinity as CaCO ₃ , mg/lit	148				

 Table 1
 Chemical characteristics of sewage wastewater

waterways which creates chances of water-borne diseases. In India, the government and scientists are facing the problem due to habit of human being to handle the sewage water. To save the environment design, operation and treatment of sludge treatment plant (STP) is the solution.

2.1 Information of Imagica Water Park, Khopoli

See Fig. 4.



Fig. 4 Sewage treatment plant flow chart

3 Result and Discussions

Membrane bioreactor (MBR) is an advanced emerging technology that can curtail the parameters of sewage such as COD, BOD, TSS, etc. Table 2 illustrate parameter of sewage before and after the treatment. Which shows that treated effluent can be used for various purpose such as gardening, flushing of toilet, etc. The residual sludge can be used as manure for agricultural purposes. Figure 5 shows the quality of effluent and manure.

IoT plays a vital role in the operation, monitoring, and maintenance of sewage treatment plants. To achieve the sustainability of the sewage, plant digital innovations

Parameter	Influent (in mg/l except pH)	Effluent (in mg/l except pH)
pH	7.95	7.77
BOD	192	2.70
COD	720	8.18
TSS	321	3.51

 Table 2
 Parameters of sewage before and after treatment



Fig. 5 Water quality and manure after the MBR treatment

26

Application of Artificial Intelligence and IoT to Membrane Bioreactor ...

were carried out which sense the analysis of the collected data, and the operational treatment technology. The programmable logic controllers (PLC), process control station, and optical fiber sensor were implemented to control the operation. Supervisory Control and Data Acquisition (SCADA) method was executed to evaluate the overall functioning of the plant. PLC, remote terminal units (RTU) interpreted the gathered information about effluent characteristics, analyze the real-time data from the connected numerous sensors and transmit it to the field instrumentation. With the help of a real-time sensor and SCADA online monitoring of pH of effluent, total suspended solids variation during the process. The quality of effluent depends upon the amount of dissolved oxygen present in the effluent. Degradation of effluent is depending upon the microorganism such as aerobic bacteria which consume the oxygen and curtail the parameters of the effluent. Chemical oxygen demand (COD) is the crucial constraints which elaborate the sewage wastewater quality. SCADA application helps to monitor the parameters of COD.

References

- Adeloye, A. J., & Dau, Q. V. (2019). Hedging as an adaptive measure for climate change induced water shortage at the Pong reservoir in the Indus Basin Beas River, India. *Science of the Total Environment*, 687, 554–566.
- Ahmed, A. N., Othman, F. B., Afan, H. A., & Elsha, A. (2019). Machine learning methods for better water quality prediction. *Journal of Hydrology*, 578.
- Al Aani, S., Bonny, T., Hasan, S. W., & Hilal, N. (2019). Can machine language and artificial intelligence revolutionize process automation for water treatment and desalination. *Desalination*, 458, 84–96.
- Bozkurt, H., van Loosdrecht, M. C. M., Gernaey, K. V., & Sin, G. (2016). Optimal WWTP process selection for treatment of domestic wastewater—A realistic full-scale retrofitting study. *Chemical Engineering Journal*, 286, 447–458.
- Bucci, V., Majed, N., Hellweger, F. L., & Gu, A. Z. (2012). Heterogeneity of intracellular polymer storage states in enhanced biological phosphorus removal (EBPR)—Observation and modeling. *Environmental Science and Technology*, 46, 3244–3252.
- Carrasco, E. F., Rodríguez, J., Pual, A., Roca, E., & Lema, J. M. (2002). Rule-based diagnosis and supervision of a pilot-scale wastewater treatment plant using fuzzy logic techniques. *Expert Systems With Applications*, 22, 11–20.
- Carrasco, E. F., Rodríguez, J., Punal, A., Roca, E., & Lema, J. M. (2004). Diagnosis of acidification states in an anaerobic wastewater treatment plant using a fuzzy based expert system. *Control Engineering Practice*, 12, 59–64.
- Chakraborty, T., Chakraborty, A. K., & Chattopadhyay, S. (2019). A novel distribution free hybrid regression model for manufacturing process efficiency improvement. *Journal of Computational and Applied Mathematics*, 362, 130–142.
- Dai, H., Chen, W., & Lu, X. (2016). The application of multi-objective optimization method for activated sludge process: A review. *Water Science and Technology*, 76, 223–235.
- Dehghani, M., Seifi, A., & Riahi-Madvar, H. (2019). Novel forecasting models for immediateshort-term to long-term influent flow prediction by combining ANFIS and grey wolf optimization. *Journal of Hydrology*, 576, 698–725.
- 11. Jia, X., Li, Z., Tan, R., Foo, D. C. Y., Majozi, T., & Wang, F. (2019). Interdisciplinary contributions to sustainable water management for industrial parks. *149*, 646–648.

- Han, H. G., Liu, Z., Guo, Y. N., & Qiao, J. F. (2018). An intelligent detection method for bulking sludge of wastewater treatment process. *Journal of Process Control*, 68, 118–128.
- Han, H. G., Zhang, L., Liu, H. X., & Qiao, J. F. (2018). Multiobjective design of fuzzy neural network controller for wastewater treatment process. *Applied Soft Computing Journal*, 67, 467–478.
- Hernández-Del-Olmo, F., Llanes, F. H., & Gaudioso, E. (2012). An emergent approach for the control of wastewater treatment plants by means of reinforcement learning techniques. *Expert Systems With Applications*, 39, 2355–2360.
- Huang, M., Han, W., Wan, J., Ma, Y., & Chen, X. (2016). Multi-objective optimisation for design and operation of anaerobic digestion using GA-ANN and NSGA-II. *Journal of Chemical Technology and Biotechnology*, 91, 226–233.
- Huang, M., Ma, Y., Wan, J., & Chen, X. (2015). A sensor-software based on a genetic algorithmbased neural fuzzy system for modeling and simulating a wastewater treatment process. *Applied Soft Computing Journal*, 27, 1–10.
- Podder, M. S., & Majumder, C. B. (2016). The use of artificial neural network for modelling of phycoremediation of toxic elements As(III) and As(V) from wastewater using *Botryococcus* braunii. Spectrochimica Acta Part A: Molecular and Biomolecular Spectroscopy, 155, 130–145.
- Zhang, X. P. S. (2017). To the victor go the spoils: AI in financial markets [perspectives]. *IEEE* Signal Processing Magazine, 34, 176–176.
- Zhang, Y., Gao, X., Smith, K., Inial, G., Liu, S., Conil, L. B., & Pan, B. (2019). Integrating water quality and operation into prediction of water production in drinking water treatment plants by genetic algorithm enhanced artificial neural network. *Water Research*, 164, 114888.
- Zhang, Y., & Pan, B. (2014). Modeling batch and column phosphate removal by hydrated ferric oxide-based nanocomposite using response surface methodology and artificial neural network. *Chemical Engineering Journal*, 249, 111–120.
- 21. Zhang, Z., Kusiak, A., Zeng, Y., & Wei, X. (2016). Modeling and optimization of a wastewater pumping system with data-mining methods. *Applied Energy*, *164*, 303–311.
- 22. Zhao, L., Deng, J., Sun, P., Liu, J., Ji, Y., Nakada, N., Qiao, Z., Tanaka, H., & Yang, Y. (2018). Nanomaterials for treating emerging contaminants in water by adsorption and photocatalysis: Systematic review and bibliometric analysis. *Science of the Total Environment*, 627, 1253– 1263.

Emerging Materials and Technologies

Shape Memory Polymer Composites

Characterization and Modeling



Nilesh Tiwari and Kanif M. Markad



opyrighted mater

Designed cover image: © Shutterstock

MATLAB® is a trademark of The MathWorks, Inc. and is used with permission. The MathWorks does not warrant the accuracy of the text or exercises in this book. This book's use or discussion of MATLAB® software or related products does not constitute endorsement or sponsorship by The MathWorks of a particular pedagogical approach or particular use of the MATLAB® software.

First edition published 2024 by CRC Press 2385 NW Executive Center Drive, Suite 320, Boca Raton FL 33431

and by CRC Press 4 Park Square, Milton Park, Abingdon, Oxon, OX14 4RN

CRC Press is an imprint of Taylor & Francis Group, LLC

© 2024 Nilesh Tiwari and Kanif M. Markad

Reasonable efforts have been made to publish reliable data and information, but the author and publisher cannot assume responsibility for the validity of all materials or the consequences of their use. The authors and publishers have attempted to trace the copyright holders of all material reproduced in this publication and apologize to copyright holders if permission to publish in this form has not been obtained. If any copyright material has not been acknowledged please write and let us know so we may rectify in any future reprint.

Except as permitted under U.S. Copyright Law, no part of this book may be reprinted, reproduced, transmitted, or utilized in any form by any electronic, mechanical, or other means, now known or hereafter invented, including photocopying, microfilming, and recording, or in any information storage or retrieval system, without written permission from the publishers.

For permission to photocopy or use material electronically from this work, access www.copyright. com or contact the Copyright Clearance Center, Inc. (CCC), 222 Rosewood Drive, Danvers, MA 01923,978-750-8400. For works that are not available on CCC please contact mpkbookspermissions@ tandf.co.uk

Trademark notice: Product or corporate names may be trademarks or registered trademarks and are used only for identification and explanation without intent to infringe.

Library of Congress Cataloging-in-Publication Data Names: Tiwari, Nilesh, author. | Markad, Kanif M., author. Title: Shape memory polymer composites : characterization and modeling / Nilesh Tiwari and Kanif M. Markad. Description: First edition. | Boca Raton, FL : CRC Press, 2024. | Includes bibliographical references and index. Identifiers: LCCN 2023024118 (print) | LCCN 2023024119 (ebook) | ISBN 9781032489940 (hardback) | ISBN 9781032490007 (paperback) | ISBN 9781003391760 (ebook) Subjects: LCSH: Shape memory polymers. | Polymeric composites. Classification: LCC TA455.P585 .T59 2024 (print) | LCC TA455.P585 (ebook) | DDC 620.1/92–dc23/eng/20230629 LC record available at https://lccn.loc.gov/2023024118 LC ebook record available at https://lccn.loc.gov/2023024119

ISBN: 978-1-032-48994-0 (hbk) ISBN: 978-1-032-49000-7 (pbk) ISBN: 978-1-003-39176-0 (ebk)

DOI: 10.1201/9781003391760

Typeset in Times by codeMantra

Croppighted maintak

Contents

About the A	uthors			x			
Chapter 1	Intro	Introduction to Shape Memory Polymer 1					
	1.1 Discovery of Shape Memory Effect						
	1.2	Classi	fication of Shape Memory Materials	2			
	1.3	Shape	Memory Effect in Polymers				
	1.4	Governing Principles of Shape Memory Effect in Polymers 4					
	1.5	1.5 Molecular Mechanism of the Thermally Induced					
		Shape	Memory Effect				
		1.5.1	Transition Temperature	7			
	1.6	The R	ole of Crystallization	7			
	1.7	Shape	Memory Characterization	9			
		1.7.1	Morphology-Dependent Function	13			
	1.8	Applic	ation	15			
	1.9	Outlook Challenges					
	1.10	Shape Memory Alloy					
	1.11	Comparison between Shape Memory Alloy and					
		Shape	Memory Polymer				
	Refer	rences		23			
Chapter 2	Shap	e Memo	ry Polymer Composites	25			
	2.1	Comp	osites				
	2.2	Fiber.					
		2.2.1	Glass Fibers				
		2.2.2	Carbon Fiber				
		2.2.3	Aramid Fiber				
		2.2.4	Extended-Chain Polyethylene Fibers				
		2.2.5	Natural Fibers				
	2.3	Matrix	<i>.</i>				
	2.4	Shape	Memory Polymer Composites				
		2.4.1	Shape Memory Fiber-Reinforced Polymer				
			Composites				
		2.4.2	Shape Memory Polymer Nanocomposites				
		2.4.3	Shape Memory Hybrid Composites				

vii

Cappinghmid minurbat

Chapter 3	Fabr	ication an	nd Characterization	49
	3.1	Basic (Concepts	49
		3.1.1	Degree of Cure	50
		3.1.2	Gel Time	
	3.2	Bag-M	olding Process	52
	3.3	Compr	pression Molding	
	3.4	Pultrus	ion	55
	3.5	Filame	nt Winding	56
		3.5.1	Winding Strategies	
	3.6	Resin 7	Fransfer Molding	59
	3.7	Charac	terization	61
		3.7.1	Tensile Testing	61
		3.7.2	Compressive Testing	63
		3.7.3	Flexural Testing	66
		3.7.4	In-Plane Shear Testing	67
		3.7.5	Interlaminar Shear Strength Testing	69
		3.7.6	Fatigue Testing	
		3.7.7	Coefficient of Thermal Expansion	75
		3.7.8	Thermal Conductivity	
		3.7.9	Crosslink Density in Shape Memory Polymers	77
		3.7.10	Nuclear Magnetic Resonance Spectroscopy	
		3.7.11	Thermal Characterization	
		3.7.12	Morphological Characterization	82
		3.7.13	Scattering Techniques	85
		3.7.14	Cyclic/Thermomechanical Testing	87
	3.8	Case St	tudy: Fabrication and Characterization of	
	00000	Multipl	hase Shape Memory Composites	88
		3.8.1	Specimen Preparation	
		3.8.2	Material Characterization	88
		3.8.3	Mechanical Properties.	
		3.8.4	Thermomechanical Analysis	
		3.8.5	Shape Memory Properties	
	Refe	rences		97
Chapter 4	Mod	eling of S	Shape Memory Behavior	101
	4.1	Constit	utive Models of SMPs	101
		4.1.1	Theory of Viscoelasticity	101
		4.1.2	The Phase Transformation Theory	111
		4.1.3	The Combination Theory	119
	4.2	Micron	nechanics of Three-Phase Composites	120
		4.2.1	Equivalent Continuum Model for CNTs	121
		4.2.2	Mechanical Characterization of a Matrix	
			Embedded With CNTs	124

Copyrighted meterinal

Contents

		4.2.3	Homogenization Techniques (HTs) 12	27
		4.2.4	Chamis Approach 12	28
		4.2.5	Hahn Approach 12	29
		4.2.6	Hashin-Rosen Approach 13	90
		4.2.7	Halpin-Tsai Approach 13	31
	4.3	Buckli	ing Behavior of SMPCs 13	33
		4.3.1	Preparation of Strain in SMPC Plates 13	\$3
		4.3.2	Mathematical Investigation of the Strain	
			Energy in the SMPC Panel 13	39
		4.3.3	Shear Strain Energy in the xy Plane 13	39
		4.3.4	Shear Strain Energy in the yz Plane 14	10
		4.3.5	Stretch Strain Energy of the SMPC 14	10
		4.3.6	Strain Energy of the Fibers 14	41
		4.3.7	Microbuckling Considerations of SMPC 14	41
		4.3.8	Estimation of z, and z,	41
		4.3.9	Evaluation of the Half Wavelength for Fibers 14	12
	4.4	Case S	study: Microbuckling in Shape Memory	
		Polymer Composites		
		4.4.1	Temperature-Regulated Properties of SMPC	14
		4.4.2	Position of Neutral Strain Plane and Critical	0.0
		0121120	Buckling Plane 14	16
		4.4.3	Half Wavelength of the Fiber 14	18
	Refe	rences		19
Chapter 5	Finite Element Analysis			
	5.1	Daaka	round of Finite Floment Analysis of Compositor 15	50
	5.1	Dackg	round of Finite Element Analysis of Composites	19
	3.4	5 2 1	Strace Strain Displacement Babavier	21
		5.2.1	Stress-Strain-Displacement Benavior	10
		5.2.2	Strain Energy of Beam	00
		5.2.5	Strain Energy of the Beam Element	20
	6.2	5.2.4	Governing Equation of Bending	27
	5.5	Case 3	Rudy: Flexural Analysis of a	0
	5.4	CNI-I	Reinforced Composite Beam	80
	5.4	Case S	study: Flexural Analysis of Shape Memory	
		Polym	er Hybrid Composites (SMPHC) 1/	0
	Keterences			
Appendix 1	l: Cas	e Study:	Modeling of Shape Memory Polymer 20)3
Appendix 2	: Case	Study:	Modeling of Shape Memory Polymer Composites 20	6
Appendix 3	: Cas	e Study:	Mechanical Properties of the Shape Memory	
	Hyb	rid Con	posite Using the Halpin-Tsai Model 20)9
Index				13